



## Eaton 9395X 900-1020 kW UPS Technical Specification

Manufacturer's declaration in accordance with IEC 62040-3

IEC 62040-3 Subclause	MODEL RATING	900 kVA/kW	1020 kVA/kW
	Model catalogue reference	9395XP-900(1360)	9395XP-1020(1360)
	Number of UPM's (Uninterruptible Power Modules) and UPM rating	3 UPM's 340 kVA/kW per UPM	3 UPM's 340 kVA/kW per UPM
	UPS options:	External battery cabinets, separate battery input, integrated backfeed protection, rectifier input switch, dual feed input, G2 grade filters	
	Upgradeability	-	-
	External paralleling	Up to 4 units (16 UPM's) with HotSync technology	
5.1.1	UPS topology	Double conversion, SiC technology	
	Rated short-circuit current, Icc (fuse protection)	AC input and bypass ports: 100 kA DC-port (Common battery): 100 kA DC-port (Separate battery): 100 kA	
5.3.4	UPS performance classification	VFI-SS-111	
<b>MECHANICAL</b>			
	UPS dimensions (W x D x H) Single feed (Small IO) Dual feed (Large IO) Separate battery (Small IO) Separate battery (Large IO)	2495 x 920 x 2070 mm 2895 x 920 x 2070 mm 2495 x 980 x 2503 mm 2895 x 980 x 2503 mm	2495 x 920 x 2070 mm 2895 x 920 x 2070 mm 2495 x 980 x 2503 mm 2895 x 980 x 2503 mm
	Installed weight	2600 kg	2600 kg
	UPS cable entry	Top / bottom entry	
	UPS air flow management	Front air intake, top air exhaust	
	UPS degree of protection	IP20	
	UPS colour	Black, RAL 9005	
<b>ENVIRONMENTAL</b>			
6.5.5	Acoustic noise at 1 m in 25 °C ambient temperature	< 85 dBA in double conversion, full load < 72 dBA in double conversion, <50% load	
4.1.4	Ambient UPS storage temperature range	-25 °C to +60 °C in the protective package	
4.2.1.1 and 5.4.2.2 h	Ambient operating temperature range Nominal range Recommended	0 °C to +40 °C +20 °C to +25 °C	
		The maximum rate of temperature change shall be limited to 1.67 °C over 5 minutes (20 °C/hour), based on the ASHRAE standard 90.1-2013	
	External battery	+ 20 °C to + 25 °C recommended for optimized battery life time	



## Eaton 9395X 900-1020 kW UPS Technical Specification

Manufacturer's declaration in accordance with IEC 62040-3

	MODEL RATING	900 kVA/kW	1020 kVA/kW
4.2.1.1	Relative humidity range	5 to 95%, no condensation allowed. There shall be at least a 1.0 °C difference between the dry bulb temperature and the wet bulb temperature, at all times, to maintain a non-condensing environment.	
4.2.1.2	Operating altitude	1000 m above sea level at rated maximum ambient temperature Maximum 2000 m with 1% de-rating per each additional 100m above 1000m	
	RoHS/WEEE compliancy	Yes	

## EFFICIENCY

5.3.2 r and 6.4.1.6	Efficiency in double-conversion, rated linear load at 400 V input		
	100% load	96,5 %	96,1 %
	75% load	97,1 %	97,0 %
	50% load	97,5 %	97,5 %
	25% load	97,5 %	97,4 %
	Heat dissipation in double conversion		
	100% load	32,6 kW	41,4 kW
	75% load	20,2 kW	23,7 kW
	50% load	11,5 kW	13,1 kW
	25% load	5,8 kW	6,8 kW
	No load	-	-

## ELECTRICAL CHARACTERISTICS

## INPUT

5.2.1.a and 5.2.1 b	Rated input voltage	220/380 V; 230/400 V; 240/415 V	
	Voltage tolerance Rectifier input	rated voltage -15% / +20%	rated voltage -15% / +20%
	Bypass input	rated voltage -10% / +10%	
5.2.1 c and 5.2.1 d	Rated input frequency	50 or 60 Hz	
	Frequency tolerance	45 to 65 Hz	
5.2.2 a and 5.2.2 b	Number of input phases	3 phases + PE	
	Rectifier input	3 phases + neutral + PE	
	Bypass input		
5.2.2 d	Input power factor, double conversion mode		
	25-100% load	> 0,99	
	10-25% load	> 0,97	
5.2.2 c	Rated rectifier input current at 400 V	1556 A	1764 A
5.2.2 f	Maximum rectifier input current	1800 A	1800 A



## Eaton 9395X 900-1020 kW UPS Technical Specification

Manufacturer's declaration in accordance with IEC 62040-3

	MODEL RATING	900 kVA/kW	1020 kVA/kW
	Bypass input current, nominal/maximum	1299 A / 2280 A	1472 A / 2280 A
5.2.2 h and 5.2.2. i	Input current distortion at rated input current  Resistive load		< 3%
5.2.2 e	In-rush current		<100% of rated current
5.2.2 k	AC power distribution system compatibility		TN-S, TN, TT, IT (4-wire)
	Rectifier ramp-up, rectifier start and load step		Yes
	Backfeed protection		Yes, for both rectifier and bypass lines

## ELECTRICAL CHARACTERISTICS

## OUTPUT

5.3.2 k	Output power rating	900 kVA/kW	1020 kVA/kW
	Output power factor	pf 1.0	pf 1.0
5.3.2 f and 5.3.2 g	Number of output phases	3 phase + neutral + PE	
5.3.2 b	Rated output voltage	220/380 V; 230/400 V; 240/415 V, configurable	
5.3.2 j	Voltage transient (r.m.s)	0% during transfer from stored energy to normal mode	
5.3.2 c	Rated output frequency	50 or 60 Hz, configurable	
	Maximum slew-rate when synchronizing	0,5 Hz/s	
5.3.2 l	Overload capability @ maximum ambient temperature	10 min 110% load	10 min 110% load
	On inverter	60 sec 125% load	60 sec 125% load
		10 sec 150% load	10 sec 150% load
		300 ms >150% load	300 ms >150% load
	Overload capability @ maximum ambient temperature – On bypass	Continuous < 115% load 20 ms 1000% load	
5.3.2 m	Output current limitation, short-circuit capability	2850 A, 300 ms	2850 A, 300 ms
5.3.2 o and 5.3.2 p	Load power factor, permitted range	From 0,7 lagging to 0,9 leading without de-rating	

## BYPASS

Type of bypass	Static
Bypass rating	1360 kVA/kW
Bypass voltage range	220/380 V; 230/400 V; 240/415 V tolerance -10% / +10% of rated voltage
Transfer time break	No break
Backfeed protection	Backfeed detection. Integrated backfeed breaker is optional
Rated conditional short-circuit current, $I_{cc}$ Static bypass	100 kA (internal bypass ultra rapid fusing)



## Eaton 9395X 900-1020 kW UPS Technical Specification

Manufacturer's declaration in accordance with IEC 62040-3

	MODEL RATING	900 kVA/kW	1020 kVA/kW
	Internal static bypass ultra-rapid fuse	Bussmann, 170M7085, 3500A 690Vac	

**BATTERY CHARACTERISTICS**

5.4.2.2 d	Battery technology	Compatible with VRLA, Lithium-ion and NiCd batteries
5.4.2.2 b	Battery quantity (VRLA)	40 - 50 battery blocks, 240 - 300 cells per string
5.4.2.2 c	Battery voltage range	400-700 Vdc
5.4.2.2 f	Stored energy time	See separate declaration
5.4.2.2 o	Recharge profile	Advanced Battery Management (ABM <sup>®</sup> ) = 90% resting, 10% floating/charging (typical) OR float charge
5.4.2.2 q	End of discharge voltage (VRLA)	1.67 VPC to 1.75 VPC Configurable or automatic (load adaptive)

**COMMUNICATION CIRCUITS**

5.6	User interface & system status	Touchscreen LCD, Status LED indicators for UPS level and UPM level state and alarms
	Standard connectivity ports	4 x Mini-Slot ports for optional cards, 5 x building alarm inputs, 1 x relay output and a dedicated EPO
	Optional	Mini-Slot cards: Ethernet 10/100/1000BaseT, Web/SNMP, ModBus/Jbus TCP or RTU, Relay inputs/outputs Other: Environmental monitoring probe Gen 2 (up to 3 sensors daisy-chained)
	Cybersecurity compliance	IEC 62443-4-2, UL 2900-1
	Complete list of indications and interface devices	See User's Manual

**COMPLIANCE WITH STANDARDS**

IEC 62040-1	Safety Access	Restricted access
	Degree of protection	IP20; protection against medium sized foreign matter (incl. finger)
IEC 62040-2	Electromagnetic Compatibility	
	Immunity	EMC Category C3
	Emissions	EMC Category C3